



1~100mW

### LD PUMPED ALL-SOLID-STATE BLUE LASER

All solid state 473nm blue laser is made features of ultra compact, long lifetime, low cost and easy operating, which is used in fluorescence sensors, Raman spectrum, laser printing, holography, laser display, submarine communication, biomedicine, laser lighting show, etc.



#### SPECIFICATIONS

Wavelength (nm)	473±1
Output power (mW)	>1, 5, 10, ..., 100
Transverse mode	TEM <sub>00</sub>
Operating mode	CW
Power stability (rms, over 4 hours)	<3%, <5%, <10%
Warm-up time (minutes)	<10
M <sup>2</sup> factor	<1.2
Beam divergence, full angle (mrad)	<1.5
Beam diameter at 1/e <sup>2</sup> (mm)	~1.2
Beam height from base plate (mm)	24.8
Polarization ratio	>100:1 (0 or 90 degree)
Noise of amplitude (rms, 1~20MHz)	~30%
Operating temperature (°C)	10~35
Power supply (90~264VAC or 5V DC)	PSU-III-LCD    PSU-III-LED    PSU-III-FDA    PSU-III-OEM
Modulation option	TTL on/off, 1Hz~1KHz, 1KHz~10KHz, 10KHz~30KHz; and Analog modulation option
Expected lifetime (hours)	10000
Warranty period	1 year



MxL-III-473	PSU-III-LCD <i>High stability!</i>	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
140.8(L)×73(W)×46.2(H) mm <sup>3</sup> , 0.6kg	153 (L) × 155 (W) × 92 (H) mm <sup>3</sup> , 1.4kg	153 (L) × 155 (W) × 92 (H) mm <sup>3</sup> , 1.5kg	133 (L) × 130 (W) × 65 (H) mm <sup>3</sup> , 1.2kg	100 (L) × 62 (W) × 56 (H) mm <sup>3</sup> , 0.2kg